



TECHNICAL DATA SHEET

Product Name: Misty Imperial Wood and Gym Finish
Item Number: B00890

Description: This polyurethane finish will dry to a clear, bright, super high gloss luster and provide the ultimate in appearance and protection to fine hard wood gymnasium floors. After finish has dried, floor is scuff resistant, will not black mark, will not discolor, and is very long wearing. Maintenance is easy and fast. This product provides the most durable playing surface available. This gym finish is the companion product to our sealer and is intended to be applied over the cured seal film.

Directions: *Sealed Floors or Top Coat:* Burnish floor surface with fine grade steel wool or black floor pad. Pick all sanding debris with damp mop. Allow to dry completely. *First Coat:* Apply product in a thin, even film using a lambs wool or synthetic fiber applicator or clean, dry string mop. Rub across boards, then smooth film with wood grain. Allow to dry overnight. *Second Coat:* If second coat is desired for maximum beauty and appearance, burnish first in same manner as before and remove all debris from floor prior to application of second coat. Apply in same manner as for first coat, then allow 48 hours for complete and thorough curing. **Note:** Always use product with adequate ventilation and keep temperature above 75°F.

DANGER: Contains alliphatic petroleum distillates. Harmful or fatal if swallowed. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Extremely flammable. Use only in a well ventilated area. Do not use near heat, sparks, open flame or other sources of ignition. Do not smoke in use area. **KEEP OUT OF REACH OF CHILDREN.**

Container Disposal: Triple rinse container and discard according to local regulations.

Spill Or Leakage Procedures: Contain spill. Do not contaminate sewers, surface or ground waters. Soak up spill in inert absorbent material. Place in non-leaking containers. Seal containers & label properly for legal disposal.

Product Specifications:

USDA Classification: N/A
Color: Amber
Odor: Petroleum/Urethane
Appearance: Clear/Slightly hazy
% Solids: 40
Coverage: 500 - 600 sq. ft./gallon
Flash Point: 111°F TCC
Lbs./gal.: 7.3
Shelf Life: One year in a sealed container

CAS Numbers: Urethane Resin (Mixture): Aliphatic Petroleum Distillate 8052-41-3.
HMS Rating: Health-2; Flammability-2; Reactivity-0; Personal Protection-B.

09/01

Manufactured by:



990 Industrial Park Drive • Marietta, GA 30062
800-66-AMREP • 770-422-2071 • Fax: 770-422-1737