

SKUs covered:

DLT-W2000BLK
DLT-W3700BLK
DLT-W3700WHT
DLT-W1400BLK
DLT-W1300BLK
DLT-W2030BLK
DLT-12044118-028
DLT-12044118-087
DLT-W4400
DLT-09-015108-130
DLT-W2050BLK
DLT-12036001-028
DLT-09-029228-130
DLT-12070119-028
DLT-12070119-087
DLT-W4590
DLT-W9103

**Madalyn Lane-Redini**  
**Import Analyst**  
**United Worldwide Limited**  
**United Stationers Supply Co.**  
**(847) 699-5000 ext. 2959**  
**FAX: (847) 699-9493**  
**[mlane-redini@ussco.com](mailto:mlane-redini@ussco.com)**

**Material Safety Data Sheet**

May be used to comply with

OSHA's Hazard Communication Standard,

29 CFR 1910.1200. Standard must be

consulted for specific requirements.

U.S. Department Of Labor

Occupational Safety and Health Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072

**IDENTITY:**

Solid paint (ITEM NO: 09-015108-130、09-029228-130、09090162-028、W1000BLK、W1300BLK、W1400BLK、

Chinese name: W1575、W2000BLK、W2030BLK、W2050BLK、W3700BLK、W3700WHT、W4400、  
熱固性粉末 12044118-028、12044118-087、12037001-028、12014107-028、12036001-028、  
12051492-087、W4590、W9103、12070119-028、12070119-087、11289000、11292000)

Note: Blank Spaces are not permitted. If any item is not applicable, or no

(As Used on Label and List)

information is available, the space must be marked to indicate that.

**Section I**

Manufacturer's Name:

Emergency Telephone Number: 0755-27938666

Jiadianbao Electrical Products (Shenzhen)Co.,Ltd.

Telephone Number for Information: 0755-27938666

Address (Number, Street City, State, and ZIP Code):

Date Prepared: 11-15-04

(Region No. 117)Feng Huang Gang Village, Xin An, Baoan

Signature of Preparer(optional): Andy Shum

County, Shenzhen City, Guangdong Province, China

**Section II – Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Nonylphenol and ethoxylates				0.001
Bisphenol A				0.001~0.002
Lead and organic lead compounds				0.002
Hexavalent Chromium compounds				0.001~0.002

**Section III – Physical/Chemical Characteristics**

Boiling Point: 745°C

Specific Gravity (H2O=1): 1.2

Vapor Pressure (mm Hg.):

Melting Point: 265°C

Vapor Density (AIR = 1):

Evaporation Rate:

(Butyl Acetate = 1)

Solubility in Water: 0.8%

Appearance and Odor: Liquid, Fragrant Odor

**Section IV – Fire and Explosion Hazard Data**

Flash Point (Method Used):

Flammable Limits:

LEL:

UEL:

Extinguishing Media: the fire extinguisher of CO2 or the other chemistry powder.

Special fire fighting Procedures: 1. The present worker bring the nearest fire extinguisher to extinguish fire.

2. The fire department of our company arrived the fire locale to extinguish fire.

3. Ask the fire company of the local government to helping.

Unusual Fire and Explosion Hazards: None

**Section V – Reactivity Data**

Stability

Unstable ☐

Conditions to Avoid

Stable ☒

Incompatibility (Materials to Avoid):

Hazardous Decomposition or Byproducts:

Hazardous May Occur ☒  
Polymerization Will Not Occur ☒

Conditions to Avoid: make fire far away

---

### Section VI – Health Hazard Data

---

Route(s) of Entry:                      Inhalation?    Yes                      Skin?    Yes                      Ingestion?

Health Hazards (Acute and Chronic):

Breathe system sickness

Carcinogenicity:                      NTP?                      IARC Monographs?                      OSHA Regulated?

Signs and Symptoms of Exposure:

Medical Conditions:

Generally Aggravated By Exposure:

Emergency and First Aid Procedures: At first, He(she) will be sent to the First-Aid station of our company and received cure,  
If his(her) ill is bad, He(she) will be sent to the nearest hospital of the government.

---

### Section VII – Precautions for Safe Handling and Use

---

Step to Be Taken in Case Material Is Released or Spilled:

The worker who only had been trained to rightly use the Chemical material can operate it.

Waste Disposal Method:                      It will be reclaim by The material suppliers of ours.

Precautions to Be Taken in Handling and Storing:

Ask the workers to wear the respirator, the glove and the other labor protective things.

Other Precautions:

---

### Section VIII – Control Measures

---

Respiratory Protection (Specify Type):    3M respirator

Ventilation                      Local Exhaust:    6 times/minute

Special:    7 times/minute

Mechanical (General):    6 times/minute

Other:

Protective Gloves: the leathern gloves

Eye Protection: Blinder

Other Protective Clothing or Equipment:    pinafore

Work / Hygienic Practices:

**Material Safety Data Sheet**

May be used to comply with

OSHA's Hazard Communication Standard,

29 CFR 1910.1200. Standard must be

consulted for specific requirements.

U.S. Department Of Labor

Occupational Safety and Health Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072

**IDENTITY:**

Plastic paint (ITEM NO : 09-015108-130、09-029228-130、09090162-028、W1000BLK、W1300BLK、  
Chinese name: W1400BLK、W1575、W2000BLK、W2030BLK、W2050BLK、W3700BLK、W3700WHT、  
塑膠油漆 W4400、12044118-028、12044118-087、12037001-028、12014107-028、12036001-028、  
12051492-087、W4590、W9103、12070119-028、12070119-087、11289000、11292000)

Note: Blank Spaces are not permitted. If any item is not applicable, or no

(As Used on Label and List)

information is available, the space must be marked to indicate that.

**Section I**

Manufacturer's Name:

Emergency Telephone Number: 0755-27938666

Jiadianbao Electrical Products (Shenzhen)Co.,Ltd.

Telephone Number for Information: 0755-27938666

Address (Number, Street City, State, and ZIP Code):

Date Prepared: 11-15-04

(Region No. 117)Feng Huang Gang Village, Xin An, Baoan

Signature of Preparer(optional): Andy Shum

County, Shenzhen City, Guangdong Province, China

**Section II – Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits	
			Recommended	%(optional)
Polyaromatic Hydrocarbons				0.003
Nonylphenol and ethoxylates				0.001
Hexavalent Chromium compounds				0.001–0.002

**Section III – Physical/Chemical Characteristics**

Boiling Point: 113°C

Specific Gravity (H<sub>2</sub>O=1): 0.86

Vapor Pressure (mm Hg.):

Melting Point: -81°C

Vapor Density (AIR = 1): 0.81

Evaporation Rate:

(Butyl Acetate = 1)

Solubility in Water: 0.5%

Appearance and Odor: Liquid, Fragrant Odor

**Section IV – Fire and Explosion Hazard Data**

Flash Point (Method Used): 165°C

Flammable Limits:

LEL:

UEL:

Extinguishing Media: the fire extinguisher of CO<sub>2</sub> or the other chemistry powder.

Special fire fighting Procedures: 1. The present worker bring the nearest fire extinguisher to extinguish fire.

2. The fire department of our company arrived the fire locale to extinguish fire.

3. Ask the fire company of the local government to helping.

Unusual Fire and Explosion Hazards: None

**Section V – Reactivity Data**

Stability

Unstable ☐

Conditions to Avoid

Stable ☒

Incompatibility (Materials to Avoid):

Hazardous Decomposition or Byproducts:

Hazardous

May Occur ☒

Conditions to Avoid: make fire far away.

Polymerization Will Not Occur ☒

---

## Section VI – Health Hazard Data

---

Route(s) of Entry:                      Inhalation?    Yes                      Skin?    Yes                      Ingestion?

Health Hazards (Acute and Chronic):

Breathe system sickness

Carcinogenicity:                      NTP?                      IARC Monographs?                      OSHA Regulated?

Signs and Symptoms of Exposure:

Medical Conditions:

Generally Aggravated By Exposure:

Emergency and First Aid Procedures: At first, He(she) will be sent to the First-Aid station of our company and received cure,  
If his(her) ill is bad, He(she) will be sent to the nearest hospital of the government.

---

## Section VII – Precautions for Safe Handling and Use

---

Step to Be Taken in Case Material Is Released or Spilled:

The worker who only had been trained to rightly use the Chemical material can operate it.

Waste Disposal Method:                      It will be reclaim by The material suppliers of ours.

Precautions to Be Taken in Handling and Storing:

Ask the workers to wear glove and the other labor protective things.

Other Precautions:

---

## Section VIII – Control Measures

---

Respiratory Protection (Specify Type):    3M respirator

Ventilation                      Local Exhaust:    5 times/minute

Special:    8 times/minute

Mechanical (General):    6 times/minute

Other:

Protective Gloves:    the leathern gloves

Eye Protection:    Blinder

Other Protective Clothing or Equipment:    pinafore

Work / Hygienic Practices:

**Material Safety Data Sheet**

May be used to comply with

OSHA's Hazard Communication Standard,

29 CFR 1910.1200. Standard must be

consulted for specific requirements.

U.S. Department Of Labor

Occupational Safety and Health Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072

**IDENTITY:**

**Metal paint** (ITEM NO : 09-015108-130 · 09-029228-130 · 09090162-028 · W1000BLK · W1300BLK · W1400BLK · W1575 · W2000BLK · W2030BLK · W2050BLK · W3700BLK · W3700WHT · W4400 · W12044118-028 · 12044118-087 · 12037001-028 · 12014107-028 · 12036001-028 · 12051492-087 · W4590 · W9103 · 12070119-028 · 12070119-087 · 11289000 · 11292000)

**Chinese name:**  
五金油漆

Note: Blank Spaces are not permitted. If any item is not applicable, or no

(As Used on Label and List)

information is available, the space must be marked to indicate that.

**Section I****Manufacturer's Name:**

Jiadianbao Electrical Products (Shenzhen)Co.,Ltd.

**Address (Number, Street City, State, and ZIP Code):**

(Region No. 117)Feng Huang Gang Village, Xin An, Baoan

County, Shenzhen City, Guangdong Province, China

**Emergency Telephone Number:** 0755-27938666**Telephone Number for Information:** 0755-27938666**Date Prepared:** 11-15-04**Signature of Preparer(optional):** Andy Shum**Section II – Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits	
			Recommended	%(optional)
Polyaromatic Hydrocarbons				0.003
Nonylphenol and ethoxylates				0.001
Hexavalent Chromium compounds				0.001-0.002

**Section III – Physical/Chemical Characteristics****Boiling Point:** 135°C**Specific Gravity (H2O=1):** 0.9**Vapor Pressure (mm Hg.):****Melting Point:** -87°C**Vapor Density (AIR = 1):** 0.83**Evaporation Rate:**

(Butyl Acetate = 1)

**Solubility in Water:** 1%**Appearance and Odor:** Liquid, Fragrant Odor**Section IV – Fire and Explosion Hazard Data****Flash Point (Method Used):** 210°C**Flammable Limits:****LEL:****UEL:****Extinguishing Media:** the fire extinguisher of CO2 or the other chemistry powder.**Special fire fighting Procedures:** 1. The present worker bring the nearest fire extinguisher to extinguish fire.

2. The fire department of our company arrived the fire locale to extinguish fire.

3. Ask the fire company of the local government to helping.

**Unusual Fire and Explosion Hazards:** None**Section V – Reactivity Data****Stability**Unstable ☐**Conditions to Avoid**Stable ☒**Incompatibility (Materials to Avoid):****Hazardous Decomposition or Byproducts:****Hazardous**

May Occur

☒**Conditions to Avoid:** make fire far away.**Polymerization**

Will Not Occur

☒

---

## Section VI – Health Hazard Data

---

Route(s) of Entry:                      Inhalation?    Yes                      Skin?    Yes                      Ingestion?

Health Hazards (Acute and Chronic):

Breathe system sickness

Carcinogenicity:                      NTP?                      IARC Monographs?                      OSHA Regulated?

Signs and Symptoms of Exposure:

Medical Conditions:

Generally Aggravated By Exposure:

Emergency and First Aid Procedures: At first, He(she) will be sent to the First-Aid station of our company and received cure,  
If his(her) ill is bad, He(she) will be sent to the nearest hospital of the government.

---

## Section VII – Precautions for Safe Handling and Use

---

Step to Be Taken in Case Material Is Released or Spilled:

The worker who only had been trained to rightly use the Chemical material can operate it.

Waste Disposal Method:                      It will be reclaim by The material suppliers of ours.

Precautions to Be Taken in Handling and Storing:

Ask the workers to wear glove and the other labor protective things.

Other Precautions:

---

## Section VIII – Control Measures

---

Respiratory Protection (Specify Type):    3M respirator

Ventilation                      Local Exhaust:    5 times/minute

Special:    8 times/minute

Mechanical (General):    6 times/minute

Other:

Protective Gloves: the leathern gloves

Eye Protection: Blinder

Other Protective Clothing or Equipment:    pinafore

Work / Hygienic Practices: