

#### 1. Product and Company Identification

**Material name** HP Color LaserJet Q6460A Black Print Cartridge

This product is a black toner preparation that is used in HP Color LaserJet 4730/4730mfp Use of the preparation

series printers.

Version # 05

08-31-2008 Revision date

Manufacturer information Hewlett-Packard Company

11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

**Hewlett-Packard health effects line** 

1-800-457-4209 (Toll-free within the US) 1-503-494-7199 (Direct)

General information telephone number

**HP Customer Care Line** 1-800-474-6836 1-800-474-6836 (Toll-free) 1-208-323-2551 (Direct) Aug 31, 2008 Date prepared MSDS number 309555

#### 2. Hazards Identification

Acute health effects

Skin contact Unlikely to cause skin irritation. Eye contact May cause transient slight irritation

Inhalation Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust. Low acute toxicity. Ingestion is a minor route of entry for intended use of this product. Ingestion

Potential health effects

Routes of exposure Potential routes of exposure under normal use conditions are skin, eye contact and inhalation.

Ingestion is not expected to be a primary route of exposure for this product under normal use

conditions.

Chronic health effects Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this

product as intended does not result in inhalation of excessive amounts of dust.

Carcinogenicity Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly

carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not

present this carcinogenic risk.

Other information This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU

Directive 1999/45/EC, as amended.

#### 3. Composition / Information on Ingredients

Component/substance	CAS number	% by weight	
Styrene acrylate copolymer	Trade Secret	< 85	
Wax	Trade Secret	< 15	
Carbon black	1333-86-4	< 6	
Amorphous silica	7631-86-9	< 2	

Material name Q6460A MSDS US Creation date Sep 09, 2005 Version number 5 1/6



4. First Aid Measures

First aid procedures

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for

at least 15 minutes or until particles are removed. If irritation persists, consult a physician.

Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Inhalation Move person to fresh air immediately. If irritation persists, consult a physician.

Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

5. Fire Fighting Measures

Flash point and method Not applicable

**Hazardous combustion** 

Carbon monoxide and carbon dioxide.

products Flammable properties

Like most organic material in powder form, toner can form explosive dust-air mixtures when

finely dispersed in air.

Extinguishing media

Suitable extinguishing

CO2, water, or dry chemical

media

Unsuitable extinguishing

media

None known.

Unusual fire and explosion

hazard

Like most organic material in powder form, toner can form explosive dust-air mixtures when

finely dispersed in air.

**Protection of firefighters** 

Protective equipment and

precautions for firefighters

If fire occurs in the printer, treat as an electrical fire.

Special firefighting procedures

None established.

6. Accidental Release Measures

**Personal precautions** Minimize dust generation and accumulation.

**Environmental precautions** Do not flush into surface water or sanitary sewer system. See also section 13 Disposal

considerations.

Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder

with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance

with federal, state, and local regulations.

7. Handling and Storage

Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use

with adequate ventilation. Keep away from excessive heat, sparks, and open flames.

Storage Keep out of the reach of children. Store at room temperature. Store away from strong

oxidizers. Keep tightly closed and dry.

8. Exposure Controls / Personal Protection

**Exposure limits** 

**ACGIH** 

CAS# **TWA STEL** Components Ceiling 1333-86-4 Carbon black 3.5 mg/m3 Not established Not established

Material name Q6460A MSDS US Creation date Sep 09, 2005 Version number 5 2/6



**OSHA** 

ComponentsCAS #TWASTELCeilingCarbon black1333-86-43.5 mg/m3 3.5 mg/m3 Not established<br/>TWANot established

Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH

(TWA/TLV): 10 mg/m3

Personal protective equipment

**General** No personal respiratory protective equipment required under normal conditions of use.

#### 9. Physical & Chemical Properties

Appearance Fine powder

Color Black

OdorSlight plastic odorOdor thresholdNot available.Physical stateNot available.

Form solid

Not applicable pН **Melting point** Not available. Freezing point Not available. Not applicable **Boiling point** Flash point Not applicable **Evaporation rate** Not applicable **Flammability** Not available. Not available. Flammability limits in air,

upper, % by volume

Flammability limits in air,

lower, % by volume

Not flammable

Vapor pressureNot applicableVapor densityNot applicableSpecific gravity1 - 1.2 (H2O = 1)Relative densityNot available.

**Solubility in water** Negligible in water. Partially soluble in toluene and xylene.

Partition coefficient

(n-octanol/water)

Not available.

Auto-ignition temperature Not applicable

Decomposition temperature Not available.

**Softening point** 212 - 302 °F (100 - 150 °C)

Viscosity Not applicable

### 10. Chemical Stability & Reactivity Information

Chemical stability Stable under normal storage conditions.

Conditions to avoid Imaging Drum: Exposure to light

Material nameQ6460AMSDS USCreation dateSep 09, 2005Version number 53 / 6



Incompatible materials Strong oxidizers

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Possibility of hazardous

reactions

Will not occur.

11. Toxicological Information

Oral toxicity LD50/oral/rat >2000 mg/kg; (OECD 401); Not harmful.. Not classified for acute oral toxicity

according to EU Directive 67/548/EEC and 1999/45/EC.

**Inhalation toxicity** No information available.

Not classified for acute inhalation toxicity according to EU Directive 67/548/EEC and

1999/45/EC.

Eye irritation Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Directive 67/548/EEC and as amended.

Sensitization Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and

OSHA HCS (US).

**Chronic toxicity** No information available.

**Carcinogenicity** Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans,

Group 2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation. None of the other ingredients in this preparation are classified as carcinogens according to ACGIH, EU, IARC, MAK, NTP or

OSHA.

IARC Monographs on Occupational Exposures to Chemical Agents: Evidence of carcinogenicity in humans

Amorphous silica (7631-86-9) Inadequate data. Carbon black (1333-86-4) Inadequate data.

US ACGIH Threshold Limit Values: A4 carcinogen

Carbon black (1333-86-4) Group A4 Not classifiable as a human carcinogen.

Mutagenicity

Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

Reproductive toxicity Not classified as toxic according to EU Directive 67/548/EEC and as amended, California

Prop. 65, and DFG (Germany).

Symptoms and target organs

**NIOSH Pocket Guide - Target organs** 

Amorphous silica (7631-86-9) Eyes

Amorphous silica (7631-86-9) Eyes, resp sys Amorphous silica (7631-86-9) Respiratory system

Carbon black (1333-86-4) Eyes

Carbon black (1333-86-4) Respiratory system

Carbon black (1333-86-4)

Serious health hazard. Flammable liquid. May polymerize explosively on loss of inhibitor.

12. Ecological Information

**Ecotoxicity** 96.00 Hours, LL50 > 1000 mg/l, rainbow trout

Persistence and degradability Not available.

13. Disposal Considerations

**Disposal instructions**Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely

dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal,

state, and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine

if this service is available in your location, please visit http://www.hp.com/recycle.

Material name Q6460A MSDS US

Creation date Sep 09, 2005 Version number 5 4 / 6

## 14. Transport Information

#### IATA

Not regulated as dangerous goods.

15. Regulatory Information

US EPA TSCA Inventory: All chemical substances in this product comply with all rules or **US federal regulations** 

orders under TSCA.

**CERCLA (Superfund) reportable quantity** 

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No **Hazard categories** 

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance

Section 311 hazardous

International regulations

No

chemical

All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South

Korea. New Zealand, and China.

State regulations

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Carbon black (1333-86-4)

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon black (1333-86-4) Listed: February 21, 2003 Carcinogenic.

US - Pennsylvania RTK - Hazardous Substances: Listed substance

Amorphous silica (7631-86-9) Listed. Carbon black (1333-86-4) Listed.

16. Other Information

Health: 1 **HMIS®** ratings

Flammability: 1

Physical hazard: 0

NFPA ratings Health: 1

Flammability: 1

Instability: 0

Issue date Aug 31 2008 2:24PM

Revision

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as quaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in

Section 1 above and may not meet regulatory requirements in other countries.

Material name Q6460A MSDS US 5/6



#### **Explanation of abbreviations**

**ACGIH** American Conference of Governmental Industrial Hygienists

CAS **Chemical Abstracts Service** 

**CERCLA** Comprehensive Environmental Response Compensation and Liability Act

**CFR** Code of Federal Regulations

COC Cleveland Open Cup

Department of Transportation DOT

Emergency Planning and Community Right-to-Know Act (aka SARA) **EPCRA** 

**IARC** International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

**NTP** National Toxicology Program

**OSHA** Occupational Safety and Health Administration

**PEL** Permissible Exposure Limit

**RCRA** Resource Conservation and Recovery Act

REC Recommended

Recommended Exposure Limit REL

**SARA** Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

Toxicity Characteristics Leaching Procedure **TCLP** 

Threshold Limit Value TLV

**TSCA Toxic Substances Control Act** VOC Volatile Organic Compounds

Material name Q6460A MSDS US Creation date Sep 09, 2005 6/6