

### Kidde Safety ABC Material Safety Data Sheet

			T	4
	H.M.LS. Ratings	Туре Назвод	Rating	
Date Of Preparation: 06-29-98	Minimal0	Health	1	
Supersedes: 06-01-98	Slight1 Moderate2	Flammability	0	
· ·	Scrious 3 Severe 4	Reactivity	0	
Prepared By: M. D. Brown				

L. Product Identification - Kidde ABC Dry Chemical Extinguisher CAS Number: NA

Fire Extinguisher: Kidde Safety

Manufacture

1394 South Third Street

Mebane, N.C. 29302

**Powder** Manufacture

: INDUSTRIAL DE FOSFATOS, S.A. DE C.V.

AV. DIVISION DEL GOLFO 3308 NORTE

87620 CD. VICTORIA, TAMAULIPAS

**MEXICO** 

(131) 6-1690; Fax: (131) 3-0301

Product Name: ABC Extinguisher

ABC Dry Chem. Powder Fire Extinguishing Agent

Emergency Telephone Number: CHEMTREC 1-800-424-9300

II. Ingredients	Weight %	Exposure	Limits	Hazard
Compound, CAS Number Monoammonium Phosphate, 7722-76-1 Ammonium Sulfate, 7783-20-2 Mica, 12001-26-2 Attapulgus Clay, 8031-18-3 Amorphous Silica, 7631-86-9 Methylhydrogenpolysiloxane, 68037-59-2	1 - 3 1 - 3 0.5 - 2.5 0.3 - 1.0	None None 20 mppcf None None	None None 3 mg/cm3 None 10 mg/cm3 None	None None None None None
68037-59-2	ad oversom for t	respirable dust (Du	iiance dust)	

Notes: TLV reported as 8-hour Time-Weighted average for respirable dust

III. Physical	/Chemical	Characteristics

NA Boiling Point, deg. C:

Relative Density:

NA Viscosity @ 20 deg. C:

@20/4 deg. C

(Butyl Acctate = 1)

Evaporation Rate NA Melting Point, deg. C: NA

Decomposes

mm Hg @ 20 deg. C: Vapor Density

Vapor Pressure,

(Air = 1):

Appearance and Odor: Odorless Fine Yellow Powder

NA

NA

Solubility in Water: Limited



# ABC Material Safety Data Sheet

IV. Fire And Explosi Flash Point: NA Flammable limits in Extinguishing Media Special Fire Fighting However, use standar Compressed Gas Cylic Fighters must use self entering streams or de Unusual Fire and Ex- V. Reactivity Data	air: The prod : Not Applicated procedures: d chemical fire inder with the	nict is not able The mat e fighting hazards of eathing ap	erial proc of oth opara	is not combustib edures and treat er involved mate tus. Prevent rund	le and v cylinder rials. Fo off from	or fires in enclosed fire control or dill pressed Gas Cyling	ole areas Fire ution from
Stability:		Stable	x	Conditions to avoid: Extreme Heat			
Incompatibility (Ma Hazardous Decomp Gas and with Ammon Hazardous Polyme Conditions to avoid	osition or By nium Compou crization : Ma : NOT APPL	products nds releas ry Occur	ses A	SCHOU AND VOICE		es Carbon Dioxide	x
Routes of Entry:	Inhalation:	Yes		Skin/Eyes:	Yes	Ingestion:	No
Health Hazard (Ac Breathing dust may i irritate the eyes. Pro	ute and Chr rritate the noi onged contac	ራል ክብለ ቸጠነ	roat a	and cause coughi slight to severe :	ing and	chest discomfort. I ation.  OSHA:	Dust may
Carcinogenicity: This material is not or	NPT:	4	inoge		1		,.l
Medical conditions Respiratory Disease Skin sensitivity Emergency and Fit Eye Contact: Flush Skin Contact: Was Inhalation: Remov	generally ag including Ast rst Aid Proce thoroughly v h contact area	gravated hma and l dures: with water with sos	tor and	exposure:  hysema.  It least 15 minute  I water;  hysensciousness	occurs,		edical

Notes to Physician: Symptomatic treatment only.

Page 2 of 4

immediately give 1 to 2 glasses of water and call Physician, Hospital Emergency Room or Poison Control Center for assistance. Do not induce vomiting or give anything by mouth to an unconscious person;

assistance and call a Physician. If breathing has stopped, use mouth to mouth resuscitation; Ingestion: Not expected to be a problem however, if greater than half liter (One Pint) ingested,



## ABC Material Safety Data Sheet

#### VIL Precautions For Safe Handling And Use

Steps to be taken in case Material is released or spilled:

Wear protective equipment including rubber boots rubber gloves, rubber apron and full-face piece or a half mask Air - Purifying Cartridge Respirator with particulate filters. Wear chemical goggles if a Half Mask is worn. Caution: When handling Fire Extinguisher which has accidentally discharged show care when handling and point extinguisher discharge nozzle away from the face area. For small spills sweep up and dispose of in a DOT- Approved Waste Container. For large spills Shovel into DOT - Approved Waste Containers. Keep out of sewers, storm drains surface waters and soil. Comply with all applicable Government Regulations on spill reporting handling and disposal of waste.

Waste Disposal Method:

Dispose of Contaminated product and materials used in clean-up of spills or leaks in a manner approved for this material. Consult appropriate Federal State, and Local Regulatory Agencies to ascertain proper disposal procedures. Note: Empty Containers can have residues, gases, and mist and are subject to proper waste disposal, as above.

Precautions To Be Taken Handling and Storing:

Store in a cool, dry, well -ventilated place away from acidic and ammonium compounds. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Do not cut, grind, weld, or drill on or near product containers. Containers, even those that have been emptied, will retain residue and vapors. Always obey hazard warnings and handle empty containers as if they were full.

Other Precautions:

Report spills as required to appropriate authorities. U.S. Coast Guard Regulations require immediate reporting of spills that could reach any Waterway including intermittent dry creeks. Report spills to Coast Guard telephone number (800) 424 - 8802. In case of accident or road spill notify Chemtrec telephone number (800) 424-9300.

#### VIII. Control Measures

Respiratory Protection:

Use dust respirator approved by NIOSH/MSHA schedule TC-84A for dusty conditions or if dust levels exceed established standards. No special requirements under ordinary conditions of use and with adequate ventilation.

Ventilation: Use in a well ventilated area.

Protective Equipment: Chemical type goggles, or Safety Glasses should be worn.

Work/Hygiene Practices: No special equipment required. However, good personal hygiene practices should always be followed.



### ABC Material Safety Data Sheet

#### IX. Regulatory Information

DOT Shipping Name: Fire Extinguishers

DOT Hazard Class: 2.2 (Nonflammable Compressed Gas)

DOT LD. Number: UN1044

Packing Group: N/A

U.S. OSHA Hazard Communication Standard: Product assessed in accordance with OSHA 20 CFR 1910.1200 and is determined hazardous due to cylinder being a pressurized vessel.

RCRA Information: The unused product in our opinion is not specifically listed by the EPA as hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity, and is not formulated with contaminants as determined by the toxicity characteristics leaching procedure (TCLP) however, used product may be regulated.

U.S. Superfund Amendments and Reauthorization Act (SARA) Title III: This product contains no "Extremely Hazardous Substances" SARA (311/312, formerly 302) Reportable Hazard Categories: None SARA (313) Toxic Release Program; No reportable chemicals.

Fire Extinguisher Data Prepared by:

M.D. Brown, Dir. Environmental Engineering
Walter Kidde Portable Equipment Company
1394 South Third Street
Mebane N.C. 27302
(919) 563-5911 Ext. 221
Fax: (919) 563-4582

Powder Product Data Supplied From MSDS by:

Quality Assurance Subdivision Av. Divison del Golfo 3308 87019 Cd. Victoria, Tramps. Mexico (133) 6-03-02; 3-03-03; 3-03-04 Fax: (131) 3-03-01

This product data is offered in good faith as typical and not as a product specification. The information contained herein is based on available data and is believed to be true and accurate. No warranty, expressed or implied, regarding the accuracy of this data, hazards connected with the use of the material, or the results to be obtained from the use thereof, are made. Walter Kidde Portable Equipment Company nor Industrial De Fosfatos, S. A. DE C.V. assumes no responsibility for damage or injury from the use of the product described herein.