



Revision Number: 006.0

Issue date: 08/07/2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>LOCTITE SI 7657 FLANGE SEALANT</b> known as <b>Copper Hi-Temp Gasket Sealant</b>	<b>IDH number:</b>	234922
<b>Product type:</b>	Sealant	<b>Item number:</b>	30535
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Corporation	Telephone: (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**WARNING:** CONTENTS UNDER PRESSURE.  
 FLAMMABLE AEROSOL.  
 CAUSES SKIN IRRITATION.  
 MAY CAUSE AN ALLERGIC SKIN REACTION.  
 CAUSES SERIOUS EYE IRRITATION.  
 MAY CAUSE DROWSINESS OR DIZZINESS.  
 SUSPECTED OF CAUSING CANCER.  
 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR  
 REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
CARCINOGENICITY	2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

### PICTOGRAM(S)



### Precautionary Statements

#### Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear eye and face protection. Wear protective gloves. Use personal protective

<b>Response:</b>	equipment as required.  IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
<b>Storage:</b>	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal:</b>	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Ethyl acetate	141-78-6	30 - 60
Methylene chloride	75-09-2	10 - 30
Butane	106-97-8	10 - 30
Propane	74-98-6	10 - 30
Solvent naphtha (petroleum), light aliphatic, low benzene content	64742-89-8	5 - 10
Copper	7440-50-8	1 - 5
Acetone	67-64-1	1 - 5

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
<b>Skin contact:</b>	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Symptoms:</b>	See Section 11.

### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Water should be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Unusual fire or explosion hazards:**

Contents under pressure. Do not handle or store near an open flame, heat or other sources of ignition. Exposure to temperatures above 49°C (120°F) may cause container to burst. Do not puncture or incinerate pressurized containers. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.

**Hazardous combustion products:**

Oxides of carbon. Hydrocarbons. Hydrogen chloride. Chlorine. Phosgene. Irritating vapors.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:**

Do not allow product to enter sewer or waterways.

**Clean-up methods:**

Remove all sources of ignition. Keep unnecessary personnel away. Ensure adequate ventilation. Wear appropriate personal protective equipment. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a closed container until ready for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:**

During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not puncture or incinerate pressurized containers. Refer to Section 8.

**Storage:**

Do not store above 49 °C (120 °F). Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

**For information on product shelf life contact Henkel Customer Service at (800) 243-4874.**

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethyl acetate	400 ppm TWA	400 ppm (1,400 mg/m <sup>3</sup> ) PEL	None	None
Methylene chloride	50 ppm TWA	12.5 ppm OSHA ACT 25 ppm TWA 125 ppm STEL	None	None
Butane	1,000 ppm STEL	None	None	None
Propane	Included in the regulation but with no data values. See regulation for further details	1,000 ppm (1,800 mg/m <sup>3</sup> ) PEL	None	None
Solvent naphtha (petroleum), light aliphatic, low benzene content	None	None	None	None
Copper	1 mg/m <sup>3</sup> TWA (as Cu) Dust and mist. 0.2 mg/m <sup>3</sup> TWA (as Cu) Fume.	1 mg/m <sup>3</sup> PEL (as Cu) Dust and mist. 0.1 mg/m <sup>3</sup> PEL (as Cu) Fume.	None	None
Acetone	750 ppm STEL 500 ppm TWA	1,000 ppm (2,400 mg/m <sup>3</sup> ) PEL	None	None

### Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

### Respiratory protection:

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. Use a NIOSH approved air-purifying respirator with an organic vapor cartridge.

### Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

### Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Aerosol
Color:	Golden, copper
Odor:	Solvent
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	> 38 °C (> 100.4 °F)
Melting point/ range:	Not available.
Specific gravity:	0.93 (concentrate)
Vapor density:	Not available.
Flash point:	-104 °C (-155.2 °F) ; (value for propellant).
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Evaporation rate:	Greater than butyl acetate.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	59.54 % EPA Method 24
Viscosity:	Not available.
Decomposition temperature:	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Hydrogen chloride gas. Chlorine. Phosgene. Irritating vapors.
<b>Incompatible materials:</b>	Strong oxidizing agents. Strong alkalis. Reactive metals.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Do not puncture the container. Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

<b>Relevant routes of exposure:</b>	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

## Potential Health Effects/Symptoms

<b>Inhalation:</b>	May cause dizziness, incoordination, headache, nausea, and vomiting.
<b>Skin contact:</b>	Causes skin irritation. May cause allergic skin reaction.
<b>Eye contact:</b>	Causes serious eye irritation.
<b>Ingestion:</b>	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspirated material can enter lungs and cause damage. Ingestion causes irritation and effects similar to inhalation.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Ethyl acetate	Oral LD50 (RAT) = 5.6 g/kg Oral LD50 (RABBIT) = 4.9 g/kg Oral LD50 (RABBIT) = 4.94 g/kg Inhalation LC50 (RAT, 6 h) = 16000 ppm	Blood, Central nervous system, Irritant
Methylene chloride	Oral LD50 (RAT) = 1,600 mg/kg Oral LD50 (RAT) = 3,000 mg/kg Inhalation LC50 (RAT, 15 min) = 2,000 mg/l Inhalation LC50 (RAT, 2 h) = 79 mg/l Inhalation LC50 (RAT, 6 h) = 52 mg/l Inhalation LC50 (RAT, 900 d) = 88 mg/l	Blood, Cardiac, Central nervous system, Corrosive, Irritant, Kidney, Liver, Some evidence of carcinogenicity
Butane	Inhalation LC50 (RAT, 4 h) = 658 mg/l	Cardiac, Central nervous system, Irritant
Propane	Inhalation LC50 (RAT, 15 min) = > 1,442.847 mg/l Inhalation LC50 (RAT, 15 min) = > 1,464 mg/l	Cardiac, Central nervous system, Irritant
Solvent naphtha (petroleum), light aliphatic, low benzene content	None	Irritant
Copper	None	Allergen, Blood, Central nervous system, Developmental, Gastrointestinal, Immune system, Irritant, Kidney, Liver, Mutagen, Sensory, Skin
Acetone	Oral LD50 (RABBIT) = 5,340 mg/kg Oral LD50 (RAT) = 5,800 mg/kg Oral LD50 (RAT) = 9,800 mg/kg Dermal LD50 (RABBIT) = 20,000 mg/kg Inhalation LC50 (RAT, 8 h) = 50.1 mg/l Inhalation LC50 (RAT, 4 h) = 76 mg/l	Blood, Central nervous system, Irritant, Reproductive

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ethyl acetate	No	No	No
Methylene chloride	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	Yes
Butane	No	No	No
Propane	No	No	No
Solvent naphtha (petroleum), light aliphatic, low benzene content	No	No	No
Copper	No	No	No
Acetone	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** D001: Ignitable.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Aerosols, flammable  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

#### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Aerosols, flammable, containing substances in Division 6.1, Packing Group III  
**Hazard class or division:** 2.1 (6.1)  
**Identification number:** UN 1950  
**Packing group:** None

#### Water Transportation (IMO/IMDG)

**Proper shipping name:** AEROSOLS  
**Hazard class or division:** 2.1 (6.1)  
**Identification number:** UN 1950  
**Packing group:** None

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health, Fire, Sudden Release  
**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Copper (CAS# 7440-50-8). Methylene chloride (CAS# 75-09-2).  
**CERCLA Reportable quantity:** Methylene chloride (CAS# 75-09-2) 1,000 lbs. (454 kg)  
Propane (CAS# 74-98-6) 100 lbs. (45.4 kg)  
Ethyl acetate (CAS# 141-78-6) 5,000 lbs. (2,270 kg)  
Butane (CAS# 106-97-8) 100 lbs. (45.4 kg)

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer.

#### Canada Regulatory Information

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

**Prepared by:** Sheila Gines, Regulatory Affairs Specialist

**Issue date:** 08/07/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.