

56401 56701 56801 56901

5700/ 57/0/ 5730/

401 Professional Drive Gaithersburg, MD 20879 Tel 301.590.9781

Page I of 4

# MATERIAL SAFETY DATA SHEET

NAME: LIQUID PAPER COI CAS NO: NA	KKECHUN	FĻŲ.	D (COLO		rcr-1/; tive Date:	12/10/98	Rev:	4	
A IDENTIFICATION									
Composition*		<u>%</u>	Formula:		Mixture		· ·		
Methylcyclohexane (108-87-2)	ļ		Molecular V	/eight:	NA				
Titanium Dioxide (13463-67-7) Mineral Spirits (64742-48-9) Resin, Dispersant, Colorant(s)			Synonyms:		Colored	l Correction	n Fluid	•	
Mustard Oil (57-06-7)  Masking Fragrance									
B. — PHYSICAL DATA									
Boiling Point ~212 °F ~100 °C	NA	Meltir °F	ig Point NA	°c	N/	Freezin	g Point NA	°c	
Specific Gravity (H <sub>2</sub> O=1)	Var	Vapor Density (air=1)			Vapor	Pressure @	100	°F	
~1.3	3.4			<del>lair-</del>	\	83	mm H	lg.	
Evaporation ( Butyl Acetate =1)	Saturation in Air (by volume @°F)			°F)	Autoignition Temperature  °F  °C				
>1		NA				N.	<u>A</u>	<u> </u>	
% Volatiles ~40	s	Solubility in Water Negligible				pH	NA		
Appearance/Odor Colored fluid wi	ith a pungent	solve	nt odor						
Flash Point and Test Method(s) 25°F (Closed Cu	ip) for produc	et							
Flammable Limits in Air				,			~ (	<b>6</b> /	
(% by volume)	Lower	<del></del>	1.2 %		Up	per <u>6</u> .		% 	
C. — REACTIVITY									
Stability Stable	unstab	le	Polyme	rization		may occur	<u> </u>	not occur	
Conditions to Avoid Product is flammable. Avoid conta or other ignition sources.		flamo	NA		Condid	ons to Avoid			
Incompatible Materials Strong oxidizers			Hazardous Decomposition Products  Thermal degradation may produce oxides of carbon and nitrogen and various hydrocarbons.						
* IF MULTIPLE INGREDIENTS, IN	ICLUDE CA	s NU	MBERS FO	DR EA	CH	NA=NC	T AVAIL	ABLE	
Ecotrotes Physical data, except Specific Grav	rity and % Vo	olatile	s, refers to	Methy	/lcyclohex	ane.			
						G	MEL#	1391	
						_	(A 15th and 1.	1321	

Page 2 of 4

#### D. -- HEALTH HAZARD DATA

Occupational Exposure Limits PEL's, TLV's, etc.)

8-Hour TWA's: Methylcyclohexane - 400 ppm (ACGIH)

Titanium Dioxide - 10 mg/cu m (OSHA/ACGIH)

Mineral Spirits - 300 ppm (Manufacturer recommendation)

These levels are not anticipated under foreseeable use conditions.

Warning Signals

NA

Routes/Effects of Exposure

No adverse effects anticipated from normal use. If vapors are deliberately concentrated and 1. Inhalation

inhaled (abuse), the following symptoms may occur: respiratory irritation, dizziness,

drowsiness, headache, nausea, unconsciousness, convulsions, cardiac sensitization, coma and

death. (Mustard oil is added to the product as an abuse deterrent.)

No adverse effects anticipated from normal use. Depending on amount ingested, most of the 2. Ingestion

symptoms described above may occur. Estimated LD<sub>50</sub> in rats is greater than 5 ml/kg or between 1 pint and 1 quart in humans (ref. Gosselin, Smith and Hodge, Clinical Toxicology of

Commercial Products, 5th Ed., 1984). Aspiration may result in chemical pneumonitis.

a. Contact 3. Skin

No adverse effects anticipated from normal use. Irritation may occur if contact is

prolonged/repeated.

b. Absorption

No adverse effects anticipated from normal use. Solvent can be absorbed through skin

(prolonged contact), but not likely in acutely toxic amounts.

If splashed into eye, irritation can occur. 4. Eye Contact

5. Other NA

#### E. — ENVIRONMENTAL IMPACT

1. Applicable Regulations

2. DOT Hazard Class -ORM-D

Consumer Commodity 3. DOT Shipping Name -

Environmental Effects

All components of this product comply with the U.S. Toxic Substances Control Act (TSCA).

Page 3 of 4

F. EXPOSURE CONTROL METHODS
Engineering Controls
None under normal use conditions.
Eye Protection
None under normal use conditions.
Skin Protection None under normal use conditions.
None under normal use conditions.
Respiratory Protection
None under normal use conditions.
Other
Product is non-hazardous when used as directed in an office/room with normal air circulation.
·
G WORK PRACTICES
Handling and Storage
Product is flammable. No unusual handling or storage when used as directed; when stored in large quantities
(as in warehouse), it should be in a well-ventilated, cool area, away from ignition sources.
N. J. Oliver, Mr.
Normal Clean Up Pick up spills with towels, tissues, etc.
The up spans with towns, thousand, and
Waste Disposal Methods
Dispose in accordance with applicable federal, state and local laws.
1
<u></u> . <del></del>

Page 4 of 4

	- EME	$D \cap C i$	$-\infty$	CEDI	
85	_ 1= 0/11=			V.E.E.N.	JINDO

Steps to be taken if material is released to the environment or spilled in the work area Not applicable

Fire and Explosion Hazard

Product is flammable. May produce hazardous decomposition products.

Extinguishing Media

Dry chemical, foam, carbon

dioxide.

Firefighting Procedures

In fires involving large quantities of product, use self-contained breathing apparatus. Cool fire-exposed containers with water fog/spray.

## I. — FIRST AID AND MEDICAL EMERGENCY PROCEDURES

Eyes

Flush with plenty of water. If irritation persists, obtain medical attention.

Skin

Wash with soap and water.

inhalation

No adverse effects anticipated from normal use. In an abuse situation, remove from source of exposure. Treat symptomatically. Oxygen may be administered. Seek medical attention immediately and refer to "Notes to Physician" below.

Ingestion

Consult physician.

Notes to Physician

Contains methylcyclohexane and mineral spirits which, if aspirated, may cause chemical pneumonitis. The inhalation of concentrated vapors may produce cardiac sensitization, contraindicating the use of sympathomimetic agents.

Replaces #1197, Sections A, D revised.

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

MSDS-4 (8/95)

GMEL#

1391

07/20/99 TUE 08:52 FAX 5901534



56401 56701 56801 56901 5700/ 57/0/ 5730/

401 Professional Drive Gaithersburg, MD 20879 Tel 301.590.9781

Page I of 4

## MATERIAL SAFETY DATA SHEET

name: Liquid Paper Cas no: Na	CORRECTION	FLU	m (coro		ve Date:	12/10/98	Rev:	4	
A IDENTIFICATION									
Composition*		%	Formula:		Mixture				
<del>,</del>	) <b>)</b>		Molecular V	/eight:	NA				
Methylcyclohexane (108-87-2 Titanium Dioxide (13463-67-	•	1	Synonyms:		<del></del>				
Mineral Spirits (64742-48-	•	Ì							
Resin, Dispersant, Colorant(s)			ļ		Colored	l Correctio	n Fluid		
Mustard Oil (57-06-7)									
Masking Fragrance		ł	Ĭ						
B. — PHYSICAL DATA			1						
Boiling Point		Motti	ng Point			Freezin	ng Point		
~212 °F ~100	°c NA	- °F	NA	<u>°c</u>	N/	4°F	NA	°c	
Specific Gravity (H <sub>2</sub> O=1)	Vé	por De	nsity (air=1)	ty (air=1)		Pressure @	100	°F	
~1.3			3.4			83	mm	lg	
Évaporation		Saturation In Air			Autolgnition Temperature				
( Butyl Acetate =1	) (by volume			°F)		— °F _	IA	_ °c	
>1		NA NA							
% Volatiles		Solubility in Water							
<del>-40</del>		Negligible				pH	NA		
Appearance/Odor Colored fl	uid with a pungen	t solve	nt odor						
Flash Point and Test Method(s) 25°F (Clos	sed Cup) for produ	ict							
Flammable Limits in Air									
(% by volume)	Lower		1.2 %	•	Up	per 6	.7	%	
C. — REACTIVITY									
Stability Stable		ble	Polyme	rization		may occur	wil	not occur	
Conditions to		_			<u>Conditi</u>	ons to Avoid			
Product is flammable. Avoid	contact with open	tlame	INA						
or other ignition sources.			<u> </u>						
incompatible Materials			Hazardous Decomposition Products						
Strong oxidizers			Thermal degradation may produce oxides of carbon and nitrogen and various hydrocarbons.						
			and nitro	gen and	i various	hydrocarb	ons.		
* IF MULTIPLE INGREDIEN	TS, INCLUDE CA	SNU	MBERS FO	R EAC	H	NA=N	OT AVAIL	ABLE	
Factnotes									
Physical data, except Specific	Gravity and % V	olatile	s, refers to	Methyl	cyclohex	ane.			

Page 2 of 4

## D. -- HEALTH HAZARD DATA

Occupational Exposure Limits PEL's, TLV's, etc.)

8-Hour TWA's: Methylcyclohexane - 400 ppm (ACGIH)

Titanium Dioxide - 10 mg/cu m (OSHA/ACGIH)

Mineral Spirits - 300 ppm (Manufacturer recommendation)

These levels are not anticipated under foreseeable use conditions.

Warning Signals

NA

#### Routes/Effects of Exposure

No adverse effects anticipated from normal use. If vapors are deliberately concentrated and 1. inhalation

inhaled (abuse), the following symptoms may occur: respiratory irritation, dizziness,

drowsiness, headache, nausea, unconsciousness, convulsions, cardiac sensitization, coma and

death. (Mustard oil is added to the product as an abuse deterrent.)

No adverse effects anticipated from normal use. Depending on amount ingested, most of the 2. Ingestion

symptoms described above may occur. Estimated LD<sub>50</sub> in rats is greater than 5 ml/kg or between 1 pint and 1 quart in humans (ref. Gosselin, Smith and Hodge, Clinical Toxicology of

Commercial Products, 5th Ed., 1984). Aspiration may result in chemical pneumonitis.

3. Skin

No adverse effects anticipated from normal use. Irritation may occur if contact is

prolonged/repeated.

b. Absorption

No adverse effects anticipated from normal use. Solvent can be absorbed through skin

(prolonged contact), but not likely in acutely toxic amounts.

4. Eye Contact If splashed into eye, irritation can occur.

5. Other NA

## - ENVIRONMENTAL IMPACT

#### 1. Applicable Regulations

ORM-D 2. DOT Hazard Class -

3. DOT Shipping Name -Consumer Commodity

Environmental Effects

All components of this product comply with the U.S. Toxic Substances Control Act (TSCA).

Page 3 of 4

EXPOSURE CONTROL METHODS	
ingineering Controls	
None under normal use conditions.	
ye Protection	
None under normal use conditions.	
Skin Protection	
None under normal use conditions.	
	·····
Respiratory Protection  None under normal use conditions.	
None ander Rollman use conditions.	
Other	
Product is non-hazardous when used as directed in an office/room with normal air circulation.	
G WORK PRACTICES	
Handling and Storage	
Product is flammable. No unusual handling or storage when used as directed; when stored in large quan	ıtities
(as in warehouse), it should be in a well-ventilated, cool area, away from ignition sources.	
Named Class Ho	
Normal Clean Up Pick up spills with towels, tissues, etc.	•
Normal Clean Up Pick up spills with towels, tissues, etc.	
Pick up spills with towels, tissues, etc.  Waste Disposal Methods	
Pick up spills with towels, tissues, etc.	
Pick up spills with towels, tissues, etc.  Waste Disposal Methods	
Pick up spills with towels, tissues, etc.  Waste Disposal Methods	
Pick up spills with towels, tissues, etc.  Waste Disposal Methods	

Page 4 of 4

## H. — EMERGENCY PROCEDURES

Steps to be taken if material is released to the environment or spilled in the work area Not applicable

Fire and Explosion Hazard

Product is flammable. May produce hazardous decomposition products.

Extinguishing Media

Dry chemical, foam, carbon dioxide.

Firefighting Procedures

In fires involving large quantities of product, use self-contained breathing apparatus. Cool fire-exposed containers with water fog/spray.

## I. - FIRST AID AND MEDICAL EMERGENCY PROCEDURES

Eyes

Flush with plenty of water. If irritation persists, obtain medical attention.

Skin

Wash with soap and water.

Inhalation

No adverse effects anticipated from normal use. In an abuse situation, remove from source of exposure. Treat symptomatically. Oxygen may be administered. Seek medical attention immediately and refer to "Notes to Physician" below.

Ingestion

Consult physician.

Notes to Physician

Contains methylcyclohexane and mineral spirits which, if aspirated, may cause chemical pneumonitis. The inhalation of concentrated vapors may produce cardiac sensitization, contraindicating the use of sympathomimetic agents.

Replaces #1197, Sections A, D revised.

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

MSDS-4 (8/95)

GMEL#

1391