

57001 57101 57301

401 Professional Drive Gaithersburg, MD 20879 Tel 301.590.9781

Page I of 4

# MATERIAL SAFETY DATA SHEET

NAME:	LIQUID PAPER COR	RECTION	FLU	ID (COLORS, LPC	F-17)			
CAS NO:	NA			Effective		Rev:	4	
A IFYEN	ITIFICATION							
A IUCN	TIFICATION			Formula: N	Mixture			
Composition*			<u>%</u>		VIA			
Methylcyclohexane (108-87-2)					NA .			
Titanium Dioxide (13463-67-7)				Synonyms:	•			
Mineral Spirits (64742-48-9) Resin, Dispersant, Colorant(s)				Colored Correction Fluid				
Mustard Oil (57-06-7)				Colored College I I min				
Masking Fragrance				1				
B. — PHY	SICAL DATA							
Boiling Point				ng Point	Freezing		ο	
~212	°F ~100 °C	NA NA	°F	NA °C	NA °F	<u>NA</u>	_ °c	
Specific Gravity (H <sub>2</sub> O=1)		Vapor Density (air=1)		Vapor Pressure @	100	_ °F		
~1.3		3.4		83	mm Hg			
Evaporation		Saturation in Air		Autoignition T	emperature	_		
( Butyl Acctate =1)		(by volume @ °F)		°F°C				
>1		NA NA		NA				
% Volatiles		Solubility in Water			274			
~40		Negligible		pH	NA			
Appearance/C	odor Colored fluid wi	th a pungent	solve	ent odor				
Flash Point ar Test Method(	nd 2505 (Closed Cu	-						
Flammable L					6	7 %		
(% by vo	lumė)	Lower_		1.2 %	Upper 6.			
C REA	ACTIVITY							
Stabilit	y X stable	unstat	)le	Polymerization	may occur	will no	ot occur	
Conditions to Avoid				Conditions to Avoid				
L .	lammable. Avoid contact	ct with open	flam	e NA				
or other ign	ition sources.			}				
incompatible Materials				Hazardous Decomposition Products				
Strong oxidizers				Thermal degradation may produce oxides of carbon				
{			and nitrogen and various hydrocarbons.					
* 15 04114.7	PLE INGREDIENTS, IN	CLUDE CA	C MIT	MREPS FOR EAC	H NA=NC	T AVAILA	BLE	
Footnotes			3 MU	MIBEROT ON EAC	NA-ING			
	nta, except Specific Grave	ity and % V	olatile	es, refers to Methylo	yclohexane.			
,	,				•			
1								

Page 2 of 4

### D. -- HEALTH HAZARD DATA

Occupational Exposure Limits PEL's, TLV's, etc.)

8-Hour TWA's: Methylcyclohexane - 400 ppm (ACGIH)

Titanium Dioxide - 10 mg/cu m (OSHA/ACGIH)

Mineral Spirits - 300 ppm (Manufacturer recommendation)

These levels are not anticipated under foreseeable use conditions.

Warning Signals

NA

#### Routes/Effects of Exposure

1. Inhalation No adverse effects anticipated from normal use. If vapors are deliberately concentrated and

inhaled (abuse), the following symptoms may occur: respiratory irritation, dizziness,

drowsiness, headache, nausea, unconsciousness, convulsions, cardiac sensitization, coma and

death. (Mustard oil is added to the product as an abuse deterrent.)

2. Ingestion No adverse effects anticipated from normal use. Depending on amount ingested, most of the

symptoms described above may occur. Estimated LD<sub>50</sub> in rats is greater than 5 ml/kg or between 1 pint and 1 quart in humans (ref. Gosselin, Smith and Hodge, Clinical Toxicology of

Commercial Products, 5th Ed., 1984). Aspiration may result in chemical pneumonitis.

3. Skin a. Contact

No adverse effects anticipated from normal use. Irritation may occur if contact is

prolonged/repeated.

b. Absomtion

No adverse effects anticipated from normal use. Solvent can be absorbed through skin

(prolonged contact), but not likely in acutely toxic amounts.

4. Eye Contact If splashed into eye, irritation can occur.

5. Other NA

## E. - ENVIRONMENTAL IMPACT

1. Applicable Regulations

2. DOT Hazard Class - ORM-D

3. DOT Shipping Name - Consumer Commodity

Environmental Effects

All components of this product comply with the U.S. Toxic Substances Control Act (TSCA).

Page 3 of 4

F EXPOSURE CONTROL METHODS
Engineering Controls
None under normal use conditions.
Eye Protection
None under normal use conditions.
Skin Protection
None under normal use conditions.
The second secon
Respiratory Protection
None under normal use conditions.
Other
Product is non-hazardous when used as directed in an office/room with normal air circulation.
G WORK PRACTICES
Handling and Storage
Product is flammable. No unusual handling or storage when used as directed; when stored in large quantities
(as in warehouse), it should be in a well-ventilated, cool area, away from ignition sources.
(as in waterways), it should be in a west-vestimated ever many stray areas as
Normal Clean Up
Pick up spills with towels, tissues, etc.
Waste Disposal Methods
Waste Disposal Methods Dispose in accordance with applicable federal, state and local laws.

Page 4 of 4

Steps to be taken if material is released to the environment or spilled in the work area Not applicable

Fire and Explosion Hazard

Product is flammable. May produce hazardous decomposition products.

Extinguishing Media

Dry chemical, foam, carbon dioxide.

Firefighting Procedures

In fires involving large quantities of product, use self-contained breathing apparatus. Cool fire-exposed containers with water fog/spray.

## FIRST AID AND MEDICAL EMERGENCY PROCEDURES

Eyes

Flush with plenty of water. If irritation persists, obtain medical attention.

Skin

Wash with soap and water.

inhalation

No adverse effects anticipated from normal use. In an abuse situation, remove from source of exposure. Treat symptomatically. Oxygen may be administered. Seek medical attention immediately and refer to "Notes to Physician" below.

ingestion

Consult physician.

Notes to Physician

Contains methylcyclohexane and mineral spirits which, if aspirated, may cause chemical pneumonitis. The inhalation of concentrated vapors may produce cardiac sensitization, contraindicating the use of sympathomimetic agents.

Replaces #1197, Sections A, D revised.

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

GMEL#

1391