

1531 PAP GILLETTE | 56601 57001 | 56801 57101 | 56901 57301

401 Professional Drive Gaithersburg, MD 20879 Tel 301.590.9781

Page 1 of 4

# MATERIAL SAFETY DATA SHEET

NAME: LIQUID PAPER COR CAS NO: NA	RECTION FLUI	D (COLORS, LPC Effective		Rev:	4	
A IDENTIFICATION						
	%	Formula:	Mixture	,		
Composition*	_ <del>76_</del>	Molecular Weight:	NA			
Methylcyclohexane (108-87-2) Titanium Dioxide (13463-67-7)		Synonyms:		<del> </del>		
Mineral Spirits (64742-48-9)		,,,,				
Resin, Dispersant, Colorant(s)		Colored Correction Fluid				
Mustard Oil (57-06-7)						
Masking Fragrance						
B. — PHYSICAL DATA						
Boiling Point	Meltin	g Point	Freezi	ng Point		
~212 °F ~100 °C	NA °F	NA °c	NA °F	NA	°C	
Specific Gravity (H <sub>2</sub> O=1)		Pensity (air=1) Vapor Pressure @ 100		100	°F	
~1.3	3	3.4		mm Hg	_	
		ation in Air Autoignition Temperature			<del></del>	
( Butyl Acetate =1)	\	(by volume @ °F)			°Ç	
>1	NA		P	JA	<del></del>	
% Volatiles ~40	Solubility in Water Negligible		pH	NA		
	th a pungent solve	nt odor			<del></del>	
Flash Point and Test Method(s) 25°F (Closed Cu	p) for product					
Flammable Limits in Air (% by volume)	t avvan	2 %	Upper 6	5.7 %		
	Lower	7.2	Obbei	7.7		
C REACTIVITY						
Stability Stable	unstable	Polymerization	may occur	will not	occur	
Conditions to Avoid Product is flammable. Avoid contact	ot with onen flame	NA	Conditions to Avoid			
or other ignition sources.	ot with open timite					
			A Donas - Altion I	Daniel and a		
Incompatible Materials		Hazardous Decomposition Products Thermal degradation may produce oxides of carbon				
Strong oxidizers		and nitrogen and various hydrocarbons.				
			<b>-</b>			
* 15 16 18 18 18 18 18 18 18 18 18 18 18 18 18	ICLUDE AAC WW	WOUTE FOR FAC	NA=M	OT AVAILAE	81 E	
* IF MULTIPLE INGREDIENTS, IN	GLUDE CAS NUI	VIBERS FOR EAC	NA-N	AVAILAL		
Physical data, except Specific Grave	ity and % Volatile	s, refers to Methylo	cyclohexane.			
			-			

Page 2 of 4

## D. -- HEALTH HAZARD DATA

Occupational Exposure Limits PEL's, TLV's, etc.)

8-Hour TWA's: Methylcyclohexane - 400 ppm (ACGIH)

Titanium Dioxide - 10 mg/cu m (OSHA/ACGIH)

Mineral Spirits – 300 ppm (Manufacturer recommendation)

These levels are not anticipated under foreseeable use conditions.

Warning Signals

NA

#### Routes/Effects of Exposure

1. Inhelation No adverse effects anticipated from normal use. If vapors are deliberately concentrated and

inhaled (abuse), the following symptoms may occur: respiratory irritation, dizziness, drowsiness, headache, nausea, unconsciousness, convulsions, cardiac sensitization, coma and

death. (Mustard oil is added to the product as an abuse deterrent.)

2. Ingestion No adverse effects anticipated from normal use. Depending on amount ingested, most of the

symptoms described above may occur. Estimated  $LD_{50}$  in rats is greater than 5 ml/kg or between 1 pint and 1 quart in humans (ref. Gosselin, Smith and Hodge, Clinical Toxicology of

Commercial Products, 5th Ed., 1984). Aspiration may result in chemical pneumonitis.

3. Skin a. Contact

No adverse effects anticipated from normal use. Irritation may occur if contact is

prolonged/repeated.

b. Absorption

No adverse effects anticipated from normal use. Solvent can be absorbed through skin

(prolonged contact), but not likely in acutely toxic amounts.

4. Eye Contact If splashed into eye, irritation can occur.

5. Other NA

#### E. — ENVIRONMENTAL IMPACT

## 1. Applicable Regulations

2. DOT Hazard Class - ORM-D

3. DOT Shipping Name - Consumer Commodity

Environmental Effects

All components of this product comply with the U.S. Toxic Substances Control Act (TSCA).

Page 3 of 4

Page 4 of 4

ı	<b>EMER</b>	<b>GENCY</b>	PROCED	URES

Steps to be taken if material is released to the environment or spilled in the work area Not applicable

Fire and Explosion Hazard

Product is flammable. May produce hazardous decomposition products.

Extinguishing Media

Dry chemical, foam, carbon

dioxide.

Firefighting Procedures

In fires involving large quantities of product, use self-contained breathing apparatus. Cool fire-exposed containers with water fog/spray.

# I. — FIRST AID AND MEDICAL EMERGENCY PROCEDURES

Flush with plenty of water. If irritation persists, obtain medical attention.

Wash with soap and water.

Inhalation

No adverse effects anticipated from normal use. In an abuse situation, remove from source of exposure. Treat symptomatically. Oxygen may be administered. Seek medical attention immediately and refer to "Notes to Physician" below.

Ingestion

Consult physician.

Notes to Physician

Contains methylcyclohexane and mineral spirits which, if aspirated, may cause chemical pneumonitis. The inhalation of concentrated vapors may produce cardiac sensitization, contraindicating the use of sympathomimetic agents.

Replaces #1197, Sections A, D revised.

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

MSDS-4 (8/95)

GMEL#

1391