

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION						
NFPA Rating: Health-2; Flammability-2; Reactivity-0; Special-0			HMIS Rating: Health-2; Flammability-2; Reactivity-0; Personal Protection-B			
Manufactured For: Lagasse Brothers, Inc.			DOT Hazard Classification: ORM-D			
Address: 1525 Kuebel Street			Identity (trade name as used on label):			
Address: New Orleans, LA 70123			Bravo Dust Magnet			
Phone: 800-989-7487			MSDS Number: SBA 6412 Revision- 1			
Emergency Response Number: 800-255-3924			Date Prepared: 07/12/96 Prepared By: DL			
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA			Information Calls: (770)422-2071			
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
PETROLEUM DISTILLATE		8052-41-3	No	500	100	d
ISOBUTANE		75-28-5	No	800	800	d
PETROLEUM DISTILLATE		64742-54-7	No	5mg/M3	5mg/M3	d
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: N/A			Specific Gravity (H ₂ O=1): Concentrate Only = 0.910			
Vapor Pressure: PSIG @ 70°F (Aerosols): Max. 60			Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A			
Vapor Density (Air = 1): N/E			Evaporation Rate (= 1): N/E			
Solubility in Water: Emulsifiable			Water Reactive: No			
Appearance and Odor: White, creamy spray with pine fragrance.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) NON-FLAMMABLE		Auto Ignition Temperature N/E		Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E		
FLASH POINT AND METHOD USED (non-aerosols): N/A			EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.			
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY [X] STABLE [] UNSTABLE			HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR			
Incompatibility (Mat. to avoid): Strong oxidizers.			Conditions to Avoid: Open flame, welding arcs, heat, sparks.			
Hazardous Decomposition Products: CO, CO ₂ .						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS						
ACUTE EFFECTS:						
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.						
Eye Contact: Irritation			Skin Contact: Irritation			
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause skin tumors.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.						
Protective Gloves: Latex, if skin easily irritated.			Eye Protection: Safety glasses recommended.			
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.						
Other Protective Clothing & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH TO SEWER.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Remove ignition sources. Avoid prolonged breathing of spray mist.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only