



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 755
Product name Penetrating Coil Cleaner
Effective date 29-Feb-2008
Company information Claire Manufacturing
500 Vista Ave.
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 1.0
Supersedes date 13-Nov-2007

2. Hazards Identification

Emergency overview CONTENTS UNDER PRESSURE.
Aerosol. Pressurized container may explode when exposed to heat or flame.

OSHA regulatory status Prolonged exposure may cause chronic effects.
This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects
Eyes Health injuries are not known or expected under normal use.
Skin This product may be harmful if it is absorbed through the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).
Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.
Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Target organs Kidney.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans.

Chronic effects Blood. Central nervous system. Liver. Respiratory system.
Signs and symptoms Unconsciousness. Liver injury may occur. Kidney injury may occur.
Cyanosis. Liver enlargement. Jaundice. Defatting of the skin. Irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
n-Butane	106-97-8	3 - 5
2-Butoxyethanol	111-76-2	3 - 5
Diethylene Glycol Monoethyl Ether	111-90-0	3 - 5
Propane	74-98-6	3 - 5
Non-hazardous and other components below reportable levels		> 90

4. First Aid Measures

First aid procedures
Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.
Skin contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.
Inhalation Call a physician if symptoms develop or persist.

Ingestion	Rinse mouth. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.
Notes to physician	Symptoms may be delayed.
General advice	If you feel unwell, seek medical advice (show the label where possible).

5. Fire Fighting Measures

Flammable properties	Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back.
Extinguishing media	
Suitable extinguishing media	Large Fires: Water spray, fog or regular foam. Small Fires: Dry chemical, CO2, water spray or regular foam.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Protection of firefighters	
Protective equipment and precautions for firefighters	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Personal precautions	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel away.
Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.
Methods for cleaning up	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.
Storage	Level 1 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep the container dry. Keep in an area equipped with sprinklers. Keep out of the reach of children. Use care in handling/storage.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
n-Butane	106-97-8	1000 ppm	Not established	Not established
2-Butoxyethanol	111-76-2	20 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
2-Butoxyethanol	111-76-2	50 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Engineering controls	Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.
Personal protective equipment	
Eye / face protection	Not normally needed.
Skin protection	Wear appropriate chemical resistant gloves.

Respiratory protection

No personal respiratory protective equipment normally required.

General hygiene considerations

When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Color	Colorless.
Odor	Characteristic.
Physical state	Liquid.
Form	Aerosol.
Flammability (HOC)	5.84 kJ/g estimated
Flash back	No
Pressure	45 - 55 psig @ 70F
Solubility	Partially
Flash point	-156 °F (-104.4 °C) estimated
Boiling point	208.4 °F (97.8 °C) estimated
Specific gravity	0.9697 estimated
pH	11.72 - 12.72

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition. Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known.
Hazardous decomposition products	May include oxides of oxides of carbon.

11. Toxicological Information

Acute effects	Acute LD50: 11640 mg/kg estimated, Rat, Oral Acute LD50: 11171 mg/kg estimated, Rat, Dermal Acute LC50: 101 mg/l/4h estimated, Rat, Inhalation
Sensitization	Not expected to be hazardous by OSHA criteria.
Local effects	Liver toxicity. Blood disorder may occur after ingestion. Components of the product may be absorbed into the body through the skin.
Chronic effects	Hazardous by OSHA criteria. This product may be harmful if it is absorbed through the skin. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Subchronic effects	Kidney injury may occur. Blood disorder may occur after prolonged inhalation. Blood disorder may occur after prolonged skin contact.
Neurological effects	Not expected to be hazardous by OSHA criteria.
Mutagenicity	Not expected to be hazardous by OSHA criteria.
Reproductive effects	Not expected to be hazardous by OSHA criteria.
Teratogenicity	Not expected to be hazardous by OSHA criteria.
Epidemiology	Hazardous by OSHA criteria.
Further information	Symptoms may be delayed.

12. Ecological Information

Ecotoxicity	LC50 545 mg/L estimated, Fish, 96.00 Hours, EC50 971 mg/L estimated, Daphnia, 48.00 Hours, IC50 65.76 mg/L estimated, Algae, 72.00 Hours, Components of this product have been identified as having potential environmental concerns.
--------------------	--

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F D002: Waste Corrosive material [pH <=2 or >=12.5, or corrosive to steel]
--------------------	--

Disposal instructions

Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements**Basic shipping requirements:**

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG**Basic shipping requirements:**

Proper shipping name	AEROSOLS, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Item	5F
Labels required	2.1
Transport Category	2

**IATA****Basic shipping requirements:**

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - No
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

2-Butoxyethanol	111-76-2	Present
Diethylene Glycol Monoethyl Ether	111-90-0	Environmental hazard
n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information**HMIS® ratings**

Health: 1*
Flammability: 2
Physical hazard: 0

Prepared by

Regulatory Compliance

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date

29-Feb-2008

MSDS sections updated

Composition / Information on Ingredients: Ingredients