

G•O•E•S®

**Ready to Use Spray
Multi-Purpose Spray-On/Wipe-Off Cleaner**

POWER . . . FOR HEAVY-DUTY MAINTENANCE CLEANING . . .

FRANKLIN G • O • E • S is a special formulation of synthetic detergents, sequestrant, emulsifiers, water-miscible penetrant, and alkaline builder developed to remove heavy soil, wax, oil and grease from all surfaces. Triple action **G • O • E • S** uses penetration, saturation and emulsification to tackle tough cleaning jobs . . . especially where grease and oil are found!

BIG JOBS MADE EASY.

Use **G • O • E • S** for equipment maintenance, too! On tools and machinery. On cars, trucks, buses and other transportation equipment, cleaning action is fast!

HANDY FOR SPOT CLEANING OR RAPID CLEANING OF ANY AREA NECESSITATING MINIMUM DWELL TIME, SUCH AS VERTICAL SURFACES, KICK AND SWITCHPLATES.

FOR CLEANING GREASE FILTERS, DUCTS, REFUSE CONTAINERS OR OTHER TOUGH GREASE REMOVAL JOBS.

SPRAY APPLICATION TO FLOORS, TRUCK OR BUS CHASSIS AND OTHER METAL SURFACES.

FOR GENERAL OVERALL CLEANING OF PAINTED WALLS AND WOODWORK.

ALSO FOR CERAMIC OR PORCELAIN SURFACES, OR LIGHT DUTY CLEANING.

HOW TO USE

Use a medium to heavy spray. Spray on, and then wipe immediately with a clean cloth or sponge. Rinse with clear water.

FRANKLIN G•O•E•S®

DETAILED REQUIREMENTS

pH:	13.0 ± 0.2
Color:	Rose
Odor:	Mild
Solubility:	Complete
Rinsing Properties:	Free-rinsing
Foam Level:	Moderate
Container Stability:	Stable in closed container at room temperature for 2 years minimum.

IMPORTANT

Use only as directed. Do not mix with anything unless recommended, since harmful conditions and poor performance could result.

All floors are slippery when wet. To prevent falls, exercise care when working and block off traffic with "Danger" signs until the polish or floor are **completely** dry.

Contains 2-Butoxy ethanol which may cause damage to the liver, kidneys and blood-forming system based on laboratory animal data. May be harmful if absorbed through the skin or swallowed in large quantities.

DANGER! Do not get in eyes, on skin, or on clothing. Avoid breathing vapors. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Do not taste or swallow.

FIRST AID: If in eyes or skin: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. **If inhaled:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. **If swallowed:** Do NOT induce vomiting. Give water to drink. Get medical attention. **NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.**

For Professional Sanitary Maintenance Use Only.

Before using, read Material Safety Data Sheet (MSDS) for this material.

¡IMPORTANTE AVISO! Si Ud. no sabe como se usa este producto pida ayuda de su capataz o supervisor.

FOR CHEMICAL EMERGENCY
Spill, Leak, Fire, Exposure or Accident
CALL CHEMTREC DAY OR NIGHT
800-424-9300

RIGHT TO KNOW INFORMATION FOR NJ AND PA

Water	7732185
2-Butoxy ethanol	111762
Sodium metasilicate	6834920
Nonyl phenoxy poly (ethyleneoxy) ethanol	9016459
Sodium xylene sulfonate	1300727

Purex Industrial (614) 387-6200

F4650

KEEP OUT OF REACH OF CHILDREN

FRANKLIN MAINTENANCE PRODUCTS ARE DISTRIBUTED BY:



Franklin
MAINTENANCE PRODUCTS

Purex Industrial

Division of IVAX Industries, Inc.
Rock Plaza III, 101 Rock Road
Horsham, Pennsylvania 19044
(215) 957-8800

IVAX
Industries, Inc.